

Bandpass Filters IR > 6680nm - 10999nm

Generall Parameters

Transmission:	> 50%
Blocking:	< 0.1% of UV
Ø 25.4mm	CA > 22mm
A: up to 3200nm	B: up to 3500nm
C: up to 6500nm	D: up to FIR
E: up to 10500nm	F: up to 16500nm
E** : up to 13000nm	

Stock program

ATTENTION! Other sizes are, due to our flexible stock program available at short notice mostly without an price increase.

CWL [nm]	HW [nm]	Order No.: ø25,4mm CA > 22mm
6680 ±25	110 ±35	bk-1080-030E
6700 ±40	80 ±20	bk-10600-370E
6720 ±50	100 ±25	bk-6720-100E
6810 ±25	100 ±20	bk-6810-100E
6845 ±30	100 ±20	bk-6845-100E
7180 ±30	105 ±20	bk-7180-105E
7230 ±30	105 ±20	bk-7230-105E
7355 ±25	175 ±25	bk-7355-175E
7600 ±50	150 ±30	bk-7600-150E
7625 ±50	160 ±30	bk-7625-160E
7720 ±80	175 ±30	bk-7720-175E
7800 ±100	170 ±40	bk-7800-170E
7900 ±80	175 ±30	bk-7900-175E
8200 ±80	250 ±30	bk-7900-250E**
8550 ±80	120 ±20	bk-8550-120E**
8600 ±80	180 ±30	bk-8600-180E**
8640 ±30	115 ±15	bk-8640-115E
8700 ±80	180 ±30	bk-8700-180E**
8780 ±80	345 ±50	bk-8780-345E**
8800 ±80	180 ±30	bk-8800-180E**
8950 ±90	330 ±50	bk-8950-330E
9400 ±50	220 ±40	bk-9400-220E
9520 ±100	220 ±40	bk-9520-220E
9645 ±80	220 ±40	bk-9645-220E**
10500 ±150	385 ±80	bk-10500-385F
10600 ±60	240 ±50	bk-10600-240F
10600 ±150	370 ±80	bk-10600-370F